

Link do produktu: <https://monitory-reklamowe.com/monitor-reklamowy-samsung-db43j-p-110.html>

Monitor reklamowy Samsung DB43J



Cena brutto	4 496,50 zł
Cena netto	3 655,69 zł
Dostępność	Dostępny
Producent	Samsung

Opis produktu

Monitor reklamowy Samsung DB43J

Features

Expand Engagement Potential

The DBJ series elevates audience communication minus the hassle and financial burden. High-quality graphic presentation, 16/7 performance and an easy-to-use content management solution make for a powerful and efficient tool to deliver captivating messages.

Leverage All-in-One Capability

The embedded MagicInfo Player S5 simplifies the content deployment process by providing a convenient solution for seamless content scheduling and eliminating the need for a separate media player.

Enjoy Operational Flexibility

With the TIZEN 3.0 operating system, users receive a host of business-critical capabilities, ranging from advanced graphic presentation, easy open platform application development to remote management.

Protect Valuable Assets

The powerful Knox security platform provides the most rigorous defense possible. A rigid, three-layer architecture offers airtight protection at the application, platform and system layers, restricting access to content and hardware.

Extend Beyond Display

Eliminate the need to have a PC nearby to manage content. All you need is a keyboard and mouse to access and remotely control your off-site PC from the display through a secure connection.

Panel:

Diagonal Size: 43"
Type: 60Hz D-LED BLU
Resolution: 1920*1080 (Full HD)
Pixel Pitch(mm): 0.16333(H) x 0.49005(V)
Active Display Area(mm): 940.89(H) x 529.25(V)
Brightness(Typ.): 300 nit
Contrast Ratio: 3000:1
Viewing Angle(H/V): 178:178
Response Time(G-to-G): 8ms
Display Colors: 16.7 M
Color Gamut: 72%
Operation Hour: 16/7
Haze: 2%
Dynamic C/R: MEGA
H-Scanning Frequency: 30 ~ 81kHz
V-Scanning Frequency: 48 ~ 75Hz
Maximum Pixel Frequency: 148.5MHz
Speaker Type: Built in Speaker(10W + 10W)
Input:
Video: HDMI 1.4 (2), DVI-D
HDCP: HDCP 2.2
Audio: Stereo Mini Jack, DVI/HDMI/Audio(Common)
USB: USB 2.0 x 1
Output:
Audio: Stereo Mini Jack
External Control: RS232C(in/out) thru stereo jack, RJ45
Tuner: Yes(only for NA)
Type: Internal
Power Supply: AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption:
Max[W/h]: 99
Typical[W/h]: (W/W)67, (US)38, (KR)67
BTU(Max): 337.6
Sleep mode: less than 0.5W
Off mode: 0
Dimension (mm):
Set: 985.5 X 574.8 X 73.4
Package: 1099 X 672 X 156
Weight (kg):
Set: 7.9
Package: 11.6
VESA Mount (mm): 200*200mm
Protection Glass: N/A
Stand Type: N/A
Media Player Option Type: N/A
Bezel Width (mm): 17.3(Top), 18.3(Bottom), 21.3(Side)
Operating Temperature: 0.0 °C ~ 40.0 °C
Humidity: 10.0 % ~ 80.0 %
Key Features: Light Signage with Built-in MagicInfo S5, SSSP 5.0
Special Features: H/W : Super Clear Coating, Temperature Sensor, Pivot Display, Button Lock, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W x 2), WiFi Module Embedded S/W : Magic Clone(to USB), Auto Source Switching & Recovery, Image Rotation, RS232C/RJ45 MDC, Plug and Play (DDC2B), Built In MagicInfo Player S5, Firmware Update by Network
Internal Player:
Processor: Cortex A72 1.7GHz Quad-Core CPU
On-Chip Cache Memory: L1 Instruction Cache : 48KB L1 Data Cache : 32KB L2 Cache : 2MB
Clock Speed: 1.7GHz Quad-Core CPU
Main Memory Interface: 2.5GB LPDDR4 1400MHz 64bit
Graphics: 2D & 3D Graphic Accelerator Data Format : 32bpp Graphic resolution : 1920x1080 Output resolution : 1920x1080
Storage (FDM): 8GB (3.88GB Occupied by O/S, 4.12GB Available)
Multimedia: Video Decoder - MPEG 1/2/4, H.263, H.264/AVC - UHD H.264/AVC, VC-1, AVS/AVS+, MVC - VP8, VP9, HEVC, JPEG
Audio DSP(Decoder) - MPEG, AC3, AC4, DD, MP3 and etc
IO Ports: USB 2.0
Operating System: Tizen 3.0 (VDLinux)
Safety:
- CB (Europe) : IEC60950-1/EN60950-1 - CCC (China) : GB4943.1-2011 - PSB (Singapore) : PSB+IEC60950-1 - NOM (Mexico) : NOM-001-SCFI-1993 - IRAM (Argentina) : IRAM+IEC60950-1 - SASO (Saudi Arabia) : SASO+IEC60950-1 - BIS(India) : IEC60950-1 / IS13252 - NOM(Mexico) : Tunerless : NOM-019-SCFI-1998 - KC(Korea) : K 60950-1 - EAC(Russia) : EAC+IEC60950-1 - INMETRO(Brazil) : INMETRO+IEC60950-1 - BSMI(Taiwan) : BSMI+IEC60950-1 - RCM(Australia) : IEC60950-1/AS/NZS 60950-1 - CSA (Canada) : cUL - UL(USA) : cUL60950-1 - TUV (Germany) : CE - NEMKO (Norway) : CE

EMC:

- FCC (USA) Part 15, Subpart B Class A - CE (Europe) : EN55022:2006+A1:2007, EN55024:1998+A1:2001+A2:2003 - VCCI (Japan) : VCCI V-3 /2010.04 Class A - KCC/EK (Korea) : Tunerless : KN22 / KN24 - BSMI (Taiwan) : CNS13438 (ITE EMI) Class A / CNS13439 (AV EMI) / CNS14409 (AV EMS) CNS14972 (Digital) - C-Tick (Australia) : AS/NZS CISPR22:2009 - CCC(China) :GB9254-2008, GB17625.1-2012 - GOST(Russia/CIS) : GOST R 51317 Series, GOST 22505-97, EN55022:2006+A1:2007, EN55024:1998+A1:2001+A2:2003

Included: Quick Setup Guide, Regulatory Guide, Warranty Card, Power Cord, Remote Controller, Batteries, RS232C(IN) adapter

Optional:

Stand: STN-L4355F

Mount: WMN4070SE

Specialty: N/A

Media Player:

Media Player: SBB (Not attachable)