

Link do produktu: <https://monitory-reklamowe.com/monitor-reklamowy-samsung-dc55e-p-84.html>



Monitor reklamowy Samsung DC55E

Cena brutto	6 493,48 zł
-------------	--------------------

Cena netto	5 279,25 zł
------------	--------------------

Dostępność	Dostępny
------------	-----------------

Numer katalogowy	82
------------------	-----------

Producent	Samsung
-----------	----------------

Opis produktu

Monitor reklamowy Samsung DC55E

Features

Attract customers with optimized 16/7 performance

Engage customers and vividly display business messaging with affordable Samsung DCE Series SMART Signage, featuring high picture quality with 350 nit brightness (32": 330nit) and reliable 16/7 usage. With a slim, sleek design for extended indoor use in retail stores, Quick Service Restaurants (QSRs), small businesses and corporate conference rooms and offices, DCE Series displays stunningly present a range of immersive and timely information with captivating picture quality.

Content Auto Play in USB memory or internal memory

MagicInfo Lite Player uses a sophisticated technology to play a huge range of content including video, images, photos on demand, or from a schedule. Customers can easily play files from, or transfer between, the large internal memory or external USB devices plugged into the in-built port. The MagicInfoSlide folder on the USB memory has content that is listed in alphabetical order which is easier and convenient to use as it does not require separate schedules.

Control Displays in multiple locations easily and instantly

MagicInfo Lite solution that comes with the embedded media player extends the remote content management over network through MagicInfo server. Media contents of the USB memory stick plugged in to the back of the DCE Series displays can be scheduled to play from a remote PC.

The connection to MagicInfo server also allows remote monitoring and management of the DCE Series displays. Device information, content playback schedules, network data monitoring, time scheduling, alarms and various controls are all available remotely even without being in front of the displays.

Easily Manage digital signage with a versatile connectivity

Connect the display to other digital signage easily with interfaces based on your specific needs. The displays provide not only the essential connections businesses use the most but support for a wide range of source device types. Interfaces include HDMI, DVI, D-sub, Component and Composite input as well as RS-232C and RJ45 for extensive connectivity. In addition, DCE series has a space to attach SBB player, which can transform the signage into all-inclusive digital signage

solutions.

Panel:
Diagonal Size: 55"
Type: 60Hz D-LED BLU
Resolution: 1920*1080 (Full HD)
Pixel Pitch(mm): 0.21(H) x 0.63(V)
Active Display Area(mm): 1209.6(H) x 680.4(V)
Brightness(Typ.): 350 nit
Contrast Ratio: 5000:1
Viewing Angle(H/V): 178:178
Response Time(G-to-G): 6ms
Display Colors: 16.7 M
Color Gamut: 72%
Operation Hour: 16/7
Haze: 2%
Dynamic C/R: MEGA
H-Scanning Frequency: 30 ~ 81kHz
V-Scanning Frequency: 48 ~ 75Hz
Maximum Pixel Frequency: 148.5MHz
Speaker Type: Built in Speaker(10W + 10W)
Input: RGB, D-SUB, DVI-D
Video: HDMI1, HDMI2, Component(CVBS Common)
HDCP: HDCP 1.4
Audio: Stereo Mini Jack, RGB/DVI/HDMI/CVBS/Component Audio(common)
USB: USB 2.0 x 1
Output:
Audio: Stereo Mini Jack
External Control: RS232C(in) thru stereo jack, RJ45
External Sensor: IR
Yes(only for NA/KR)
Type: Internal
Power Supply: AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Max[W/h]: 176.0
Typical[W/h]: (W/W)115, (US)55, (KR)133
BTU(Max): 600.16
Sleep mode: less than 0.5W
Off mode: 0
Dimension (mm):
Set: 1230.6 X 706.9 X 49.9
Package: 1348 X 810 X 148
Set: 14.7
Package: 19.2
VESA Mount (mm): 400*400mm
Protection Glass: N/A
Stand Type: Foot Stand (Optional)
Media Player Option Type: Embbeded, SBB (Attachable)
Bezel Width (mm): 9.5 (Top/Side), 15.0 (Bottom)
Operating Temperature: 0.0 °C ~ 40.0 °C
Humidity: 10.0 % ~ 80.0 %
Key Features: Slim & Light LFD with Built-in MagicInfo Lite
Special Features:
H/W: Super Clear Coating, Temperature Sensor, Pivot Display, Button Lock, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W x 2) S/W: Auto Source Switching & Recovery, RS232C/RJ45 MDC, Plug and Play (DDC2B), Built In MagicInfo Lite, Firmware Update by Network
Processor: N/A
On-Chip Cache Memory: N/A
Clock Speed: N/A
Main Memory Interface: N/A
Graphics: N/A
Storage (FDM): 179MB
Multimedia: N/A
IO Ports: N/A
Operating System: Samsung Proprietary OS(VDLinux)
Safety:
- CB (Europe) : IEC60950-1/EN60950-1 - CCC (China) : GB4943.1-2011 - PSB (Singapore) : PSB+IEC60950-1 - NOM (Mexico) : NOM-001-SCFI-1993 - IRAM (Argentina) : IRAM+IEC60950-1 - SASO (Saudi Arabia) : SASO+IEC60950-1 - BIS(India) : IEC60950-1 / IS13252 - NOM(Mexico) : Tunerless : NOM-019-SCFI-1998 - KC(Korea) : K 60950-1 - EAC(Russia) :

EAC+IEC60950-1 - INMETRO(Brazil) : INMETRO+IEC60950-1 - BSMI(Taiwan) : BSMI+IEC60950-1 - RCM(Australia) :
IEC60950-1/AS/NZS 60950-1 - CSA (Canada) : cUL - UL(USA) : cUL60950-1 - TUV (Germany) : CE - NEMKO (Norway) : CE

EMC:

- FCC (USA) Part 15, Subpart B Class A - CE (Europe) : EN55022:2006+A1:2007, EN55024:1998+A1:2001+A2:2003 - VCCI
(Japan) : VCCI V-3 /2010.04 Class A - KCC/EK (Korea) : Tunerless : KN22 / KN24 - BSMI (Taiwan) : CNS13438 (ITE EMI) Class A /
CNS13439 (AV EMI) / CNS14409 (AV EMS) CNS14972 (Digital) - C-Tick (Australia) : AS/NZS CISPR22:2009 - CCC(China)
:GB9254-2008, GB17625.1-2012 - GOST(Russia/CIS) : GOST R 51317 Series, GOST 22505-97, EN55022:2006+A1:2007,
EN55024:1998+A1:2001+A2:2003

Included:

Quick Setup Guide, Regulatory Guide, Warranty Card, Power Cord, Remote Controller, Batteries, RS232C(IN) adapter

Stand: STN-L4655E

Mount: WMN4270SD

Specialty: CML450D (Ceiling Mount)

Media Player: SBB (Optional)