Dane aktualne na dzień: 02-11-2026 07:03

Link do produktu: https://monitory-reklamowe.com/monitor-reklamowy-samsung-qm75r-p-134.html

Monitor reklamowy Samsung QM75R



Cena brutto	**15 713,95 zł**
Cena netto	**12 775,57 zł**
Dostępność	**Dostępny**
Numer katalogowy	**132**
Producent	**Samsung**

Opis produktu

Monitor reklamowy Samsung QM75R

Features

Time to upscale your display

Samsung’s new QMR series displays cut through the clutter to deliver best-in-class UHD resolution as well as intelligent UHD upscaling and rich flawless colors with Dynamic Crystal Color all in a slim design.

Incredible 4K picture quality

Samsung’s new QMR series provides ultra high-definition 4K resolution, creating lifelike images with sharper picture quality than ever before.

Intelligent UHD upscaling

Samsung’s cutting-edge intelligent UHD upscaling technology performs edge restoration and noise reduction to deliver perfect UHD picture quality even with lower resolution content. This “future-proof” solution ensures best-in-class picture quality regardless of the original content resolution.

Dynamic Crystal Color

The QMR series features Dynamic Crystal Color, using 10 bit processing for flawless color expression, allowing viewers to enjoy a wider spectrum of colors up to one billion shades. HDR+ functionality converts standard definition content to HDR quality for sharper contrast and more vivid colors.

Perfect view with non-glare display

The QMR series features reliable, non-glare panels that provide better visibility from all angles, anytime of day allowing

businesses to deliver accurate information 24/7 in locations where clear and accurate information is crucial such as airports and commuter stations.

Slim and symmetrical design

The QMR series features an all-new symmetric design simplifying wall mounting and ensuring installation is seamless. The flat back and slim depth will ensure a display that will stand the test of time.

Clean cable management

With QMR's new cable guide feature, retailers are able to tuck away messy cables from view. This allows for a clean and visually-appealing shopping expeience for customers, even when the back of the display is visible.

Powerful, all-in-one solution

SSSP is an all-in-one solution that simplifies installation and maintenance. With Tizen 4.0, businesses can enjoy easy development, reinforced capability with multiple web formats and standards and secured protection.

Samsung Workspace secured by Knox

With security provided by Knox, the displays feature Samsung Workspace which supports wireless cloud service access and control of a PC without needing a physical connection. Samsung Workspace simplifies meeting spaces while also improving security.

WiFi and Bluetooth built-in

Built-in WiFi and Bluetooth allow for more personalized and interactive services as well as simplifying how businesses showcase content. Whether it’s to make networking simpler or enabling interactive beacon technology in-store, QMR series displays help businesses move into the future of retail.

* Image is for illustrative purposes only, specific application or program may have to be developed for the depicted usage scenario.

Industry standard certified

The QBR series guarantees dependable functionality and is environmentally sustainable. Electromagnetic compatibility (EMC) class B compliant, meeting strict safety and reliability standards for operation, the displays are also registered by EPEAT, the global ecolabel for IT.

*Image is for illustrative purposes only, specific application or program may have to be developed for the depicted usage scenario.

Panel:
Diagonal Size: 75"
Type: Edge LED BLU
Resolution: 3840*2160 (4K UHD)
Pixel Pitch(mm): 0.42975 x 0.42975
Active Display Area(mm): 1650.24 (H) x 928.26 (V)
Brightness(Typ.): 500 nit
Contrast Ratio: 4000:1
Viewing Angle(H/V): 178/178
Response Time(G-to-G): 8ms(Typ.)
Display Colors: 16.7M(True Display) 1.07B(Ditherd 10bit)
Color Gamut: 92% (DCI-P3, CIE 1976)
Operation Hour: 24/7
Haze: 44%
Dynamic C/R: MEGA
H-Scanning Frequency: 30 ~ 81kHZ
V-Scanning Frequency: 48 ~ 75HZ
Maximum Pixel Frequency: 594MHz
Speaker Type: Built in Speaker(10W + 10W)
Input:
RGB: DVI-D, Display Port 1.2 (1)

Video: HDMI 2.0 (2)
HDCP: HDCP2.2
Audio: Stereo mini Jack, DVI, HDMI
USB: USB 2.0 x 2
Output:
RGB: HDMI 2.0 (Loop-out)
Audio: Stereo mini Jack
External Control: RS232C(in/out) thru stereo jack, RJ45
External Sensor: IR
Type: Internal
Power Supply: AC 100 - 240 V~ (+/- 10 %), 50/60 Hz
Power Consumption:
Max[W/h]: 231
Typical[W/h]: 178
Rating[W/h]: 210
BTU(Max): 787.7
Sleep mode: 0.5
Dimension (mm):
Set: 1681.1 x 960.1 x 49.7
Package: 1871 x 1127 x 223
Weight (kg):
Set: 38.3
Package: 49
VESA Mount (mm): 400 X 400
Protection Glass: N/A
Stand Type: No
Media Player Option Type: N/A
Bezel Width (mm): 11.5mm(U/L/R), 12.5mm(B)
Operating Temperature: 10 ℃ ~ 40 ℃
Humidity: 10 % ~ 80 %
Key Features: UHD Signage Display Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0
Special Features: H/W: Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA), IP5x, Wi-Fi/BT S/W: Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)
Internal Player:
Processor: Coretex A72 1.7GHz Quad-Core CPU
On-Chip Cache Memory: L1 Instruction Cache : 48KB L1 Data Cache : 32KB L2 Cache : 2MB
Clock Speed: 1.7GHz
Main Memory Interface: 2.5GB LPDDR4 1.5GHz 64bit
Graphics: Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.)
Storage (FDM): 8GB (3.88GB Occupied by O/S, 4.12GB Available)
Multimedia: *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9 *Audio Decoder : AC3 (DD), MPEG
IO Ports: USB 2.0
Operating System: Tizen 4.0 (VDLinux)
Safety: 60950-1
EMC: Class B
Included: Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries
Optional:
Stand: No
Mount: WMN4277SE WMN6575SE
Specialty: CLM450K
Media Player:
Media Player: N/A

Dane techniczne monitora QM75R

Monitor Samsung **QM75R**

- *Wyświetlacz*
  - *Przekątna ekranu*75"
  - *Rodzaj panelu*New Edge, 60Hz
  - *Rozdzielczość*3,840 x 2,160
  - *Wielkość piksela (Szer. x Wys.)*0.42975(H) x 0.42975(V) (mm)
  - *Jasność (standardowa)*500
  - *Współczynnik kontrastu*4,000:1

- *Kąt widzenia (poziomy/pionowy)*178/178
- *Czas reakcji*8ms
- *Gama kolorów*92%
- *Haze*0.44 %
- *Częstotliwość skanowania w poziomie*30 ~ 81kHZ
- *Maksymalna częstotliwość piksela*594MHz
- *Częstotliwość skanowania w pionie*48 ~ 75HZ
- *Dynamiczny współczynnik kontrastu*Mega

- *Łączność*
  - *Wejście HDMI*2
  - *Wejście DP*Yes
  - *Wejście DVI*1
  - *Wejście Tuner*N/A
  - *USB*2
  - *Component In*N/A
  - *Wejście Composite*N/A
  - *Wejście RGB*N/A
  - *Wejście IR*Yes
  - *Wejście HDBaseT*No
  - *Wejście audio*Yes
  - *Wyjście audio*Stereo Mini Jack
  - *Wyjście wideo*Yes
  - *Wyjście zasilania*N/A
  - *Wejście RS232*Yes
  - *Wyjście RS232*Yes
  - *Wejście RJ45*Yes
  - *Wyjście RJ45*No
  - *WiFi*Yes
  - *3G Dongle*N/A
  - *Bluetooth*Yes

- *Pobór prądu max*
  - *Źródło zasilania*AC100-240V 50/60Hz
  - *Zużycie energii (tryb wyłączony)*N/A
  - *Zużycie energii elektrycznej (tryb wł.)*231
  - *Zużycie energii elektrycznej (tryb uśpienia)*0.5 W
- *Wymiary*
  - *Wymiary urządzenia (SxWxG)*1681.1 x 960.1 x 49.7 mm
  - *Opakowanie w mm (SxWxG)*1871 x 1127 x 223 mm
- *Waga*
  - *Waga urządzenia*38.3 kg
  - *Waga brutto (z opakowaniem)*49 kg
- *Parametry operacyjne*
  - *Temperatura*0℃~ 40℃
  - *Wilgotność*10 ~ 80%, non-condensing
- *Parametry fizyczne*
  - *Standard VESA*400 x 400 mm
  - *Szerokość obudowy*11.5(U/L/R), 12.5(D)
  - *Materiał ramy*Non-Glossy
- *Funkcje ogólne*
  - *Pamięć zewnętrzna*N/A
- *Funkcja opcjonalna*
  - *Mocowanie*WMN6575SE, WMN4277SE
  - *Podstawka*No
- *Wbudowany odtwarzacz (MagicInfo)*
  - *Obsługa pętli cyfrowej dla ścian wideo z odtwarzaczem MagicInfo*Yes
- *Ekologiczny / Funkcja Eko*
  - *Klasa efektywności energetycznej*A
- *Certyfikacja i zgodność*
  - *EMC*Class B FCC (USA) Part 15, Subpart B KCC/EK (Korea) Tuner : KN32 / KN35 Tunerless : KN32 / KN35 CE (Europe) EN55032 : 2012 or 2015 EN55024:2010 or EN 55035:2017 VCCI (Japan) VCCI CISPR32:2016 CCC(China) GB/T9254-2008 GB17625.1-2012 BSMI (Taiwan) CNS13438 (ITE EMI) CNS14336-1 (ITE Safety) CNS15663 (RoHS) C-Tick (Australia) AS/NZS CISPR32:2015 GOST(Russia/CIS) ROCT CISPR 24-2013 ROCT CISPR 22:2005
  - *Bezpieczeństwo*CB (Europe) : IEC60950-1/EN60950-1 CCC (China) : GB4943.1-2011 PSB (Singapore) : PSB+IEC60950-1 NOM (Mexico) : NOM-001-SCFI-1993 IRAM (Argentina) : IRAM+IEC60950-1 SASO (Saudi Arabia) : SASO+IEC60950-1 BIS(India) : IEC60950-1 / IS13252 NOM(Mexico) : Tuner : NOM-001-SCFI-1993 Tunerless : NOM-019-SCFI-1998 KC(Korea) : K 60950-1 EAC(Russia) : EAC+IEC60950-1 INMETRO(Brazil) : INMETRO+IEC60950-1 BSMI(Taiwan) : BSMI+IEC60950-1 RCM(Australia) : IEC60950-1/AS/NZS 60950-1 UL(USA)

: cUL60950-1 CSA (Canada) : cUL TUV (Germany) : CE NEMKO (Norway) : CE