

Link do produktu: <https://monitory-reklamowe.com/monitor-reklamowy-samsung-uh46n-e-p-116.html>

## Monitor reklamowy Samsung UH46N-E



|             |                     |
|-------------|---------------------|
| Cena brutto | <b>15 182,30 zł</b> |
| Cena netto  | <b>12 343,33 zł</b> |
| Dostępność  | <b>Dostępny</b>     |
| Producent   | <b>Samsung</b>      |

### Opis produktu

## Monitor reklamowy Samsung UH46N-E

### Features

#### **Deliver deeper visual impact**

Samsung's narrow bezel video wall features bezel-to-bezel width of 1.7mm that minimizes the visual distraction of video walls to elicit impacting imagery of products. The display produces a near-seamless picture across multiple screens without interruption, captivating and impressing customers.

#### **Amplify image clarity in any environment**

Combined with a non-glare panel, the extreme narrow bezel video wall display is designed to help businesses create memorable content presentation even under ambient light. This panel evenly distributes light throughout the screen, eliminating glare while maintaining content vibrancy and accuracy.

#### **Extend content presentation capabilities**

Samsung's video wall offers a powerful UHD viewing experience with minimal effort or additional equipment. As the first in the industry to have up to 5x5 wall configuration based on the use of DisplayPort 1.2 and HDMI ports, the display can project UHD content across multiple screens simultaneously.

#### **Share accurate and uniform content**

Samsung's multi-step factory calibration process tunes video walls to uniform brightness and color throughout multiple displays. In addition to rigorous factory calibration, users can also manage brightness and color uniformity with Samsung's Color Expert Pro, a powerful free software program.

#### **Cost saving mobile calibration with ease**

Samsung's Color Expert Pro Mobile solution provides a quick and easy video wall calibration through a mobile camera. With

---

the solution's intuitive UI, even non-expert users can adjust up to 5x5 video wall's white balance simultaneously without the need for additional equipment.

\* Some of the models may require the use of additional PC and Color Expert Pro software to calibrate the screens.

## Enjoy continuous, long-term performance

Samsung's extreme narrow bezel video walls are engineered for long-term performance, eliminating maintenance expenses for users. The display features durable panels that offset backlight discrepancies while simultaneously protecting the display against heat and dust exposure.

## Reliable content delivery for business

Designed to maintain performance in various indoor environment conditions, Samsung's video wall produces an engaging viewing experience with the elevated contrast ratios and brightness. With continuous 24/7 operations, the display enables vivid and reliable content delivery for every business need.

## All-in-one box with versatile usability

Backed by a Quad Core CPU, Signage Player Box allows for multi-source switching and a media player to coexist in a single box. Leveraging the embedded Samsung SMART Signage Platform, the box transforms video walls for faster information processing and easy content management with MagicINFO solution.

## Highly configurable wall mounts

The user-friendly special wall mounts ensure easy installation of video walls through minimal steps. Sized to the dimensions of the video wall, the wall mount allows users to install the mount first and fit into the video wall, eliminating tedious efforts to measure and adjust the wall mount size.

Panel:  
Diagonal Size: 46"  
Type: D-LED DID  
Resolution: 1920\*1080 (Full HD)  
Pixel Pitch(mm): 0.53025mm(H) \* 0.53025mm(V)  
Active Display Area(mm): 1018.08mm \* 572.67mm  
Brightness(Typ.): 700 nit  
Contrast Ratio: 4000:1  
Viewing Angle(H/V): 178/178  
Response Time(G-to-G): 8ms  
Display Colors: 8 bit - 16.7M  
Color Gamut: 72%  
Operation Hour: 24/7  
Haze: 25% (Outer Haze 23%)  
Dynamic C/R: MEGA DCR  
H-Scanning Frequency: 30kHz ~ 81kHz  
V-Scanning Frequency: 48Hz ~ 75Hz  
Maximum Pixel Frequency: 148.5MHz  
Speaker Type: N/A  
Input:  
RGB: Analog D-SUB, DVI-D, Display Port 1.2  
Video: HDMI 2.0 (2)  
HDCP: HDCP 2.2  
Audio: Stereo mini Jack  
USB: Only F/W upgrade  
Output:  
RGB: DP1.2(Loop-out)  
Audio: Stereo mini Jack  
External Control: RS232C(in/out), RJ45  
External Sensor: Detachable type(IR, Ambient)  
Type: Internal  
Power Supply: AC 100 - 240 V~ (+/- 10 %), 50/60 Hz  
Power Consumption:  
Max[W/h]: 187  
Typical[W/h]: 102  
BTU(Max): 638  
Sleep mode: less than 0.5W

---

Off mode: less than 0.5W  
Dimension (mm):  
Set: 1020.0 x 574.6 x 96.3  
Package: 1153 x 719 x 295  
Weight (kg):  
Set: 15.7kg  
Package: 21.6kg  
VESA Mount (mm): 600 \* 400 (mm)  
Protection Glass: N/A  
Stand Type: N/A  
Media Player Option Type: N/A  
Bezel Width (mm): 1.15mm(U/L), 0.55mm(R/B)  
Operating Temperature: 0 °C ~ 40 °C  
Humidity: 10 % ~ 80 %  
Key Features: Extreme Narrow Bezel  
Special Features: ACM Support(Advanced Color Management), Auto Source Switching & Recovery, Haze 25%, Temperature Sensor, RS232C/RJ45 MDC, Plug and Play (DDC2B), Video Wall(15x15(OSD)), Video Wall Daisy Chain(10x10), Pivot Display, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain(Supporting UHD Resolution, HDCP support), Smart F/W update, Clock Battery(80hrs Clock Keeping)  
Internal Player:  
Processor: N/A  
On-Chip Cache Memory: N/A  
Clock Speed: N/A  
Main Memory Interface: N/A  
Graphics: N/A  
Storage (FDM): N/A  
Multimedia: N/A  
IO Ports: N/A  
Operating System: N/A  
Safety: UL (USA) : UL 60950-1 CSA (Canada) : CSA C22.2 No. 60950-1 TUV (Germany) : EN60950-1 NEMKO (Norway) : EN60950-1 KC (Korea) : K60950-1 CCC (China) : GB4943.1-2011 PSB (Singapore) : IEC60950-1 GOST (Russia) : IEC60950-1, EN55022 SIQ (Slovenia) : IEC60950-1, EN55022 PCBC (Poland) : IEC60590-1, EN55022 NOM (Mexico) : NOM-019-SCFI-1993 IRAM (Argentina) : IEC60950-1 SASO (Saudi Arabia) : IEC60950-1  
EMC: FCC (USA) FCC Part 15, Subpart B class A CE (Europe) EN55022, EN55024 VCCI (Japan) V-3 (CISPR22) KCC (Korea) :KN22, KN24 BSMI (Taiwan) : CNS13438 (CISPR22) C-Tick (Australia) : AS/NZS3548 (CISPR22) CCC(China) :GB9254-2008, GB17625.1-2012  
Included: Quick Setup Guide, Warranty Card, DP cable, stereo to DB9 cable, Power Cord, Remote Controller, Batteries  
Optional:  
Stand: N/A  
Mount: WMN-46VD  
Specialty: N/A  
Media Player:  
Media Player: SBB(Slide In), Signage player box